

Product Specifications For C32



Ratings

Power Range	1600-1900 bhp (1193-1417 bkW)
--------------------	-------------------------------

Engine

Speed Range	2300 rpm
--------------------	----------

Emissions	IMO II, U.S. EPA Tier 3 Recreational, RCD, China Stage II
------------------	---

Aspiration	Twin Turbocharged-aftercooled
-------------------	-------------------------------

Bore	5.71 in
-------------	---------

Stroke	6.38 in
---------------	---------

Displacement	1959 in ³
---------------------	----------------------

Rotation from Flywheel End	Counterclockwise
-----------------------------------	------------------

Configuration	Vee 12, 4-Stroke Cycle diesel
----------------------	-------------------------------

Dimensions & Weights

Length	82.9 in
---------------	---------

Width	58.3 in
--------------	---------

Height	56.9 in
---------------	---------

Dry Weight	6780 lb
-------------------	---------

C32 Standard Equipment

STANDARD EQUIPMENT

ADEM IV Electronic Control Module
Air Cleaner / Fumes Disposal
Electronic Diagnostics and Fault Logging

Engine and Transmission Monitoring
Sea Water Aftercooler
Titanium Plate Heat Exchanger with Expansion Tank
Gear-driven JW and SW pumps
Water-cooled Exhaust Manifolds and Turbochargers
MEUI Fuel System
Fuel Priming and Transfer Pump
250-hr Oil Pan (Shallow Sump)
RH or LH Service Side Options

C32 Optional Equipment

OPTIONAL ATTACHMENTS

120V or 240V Jacket Water Heater
SAE A or B PTO (LH or RH rear)
75A or 105A Alternator
Spray Shielding